

## LAMP POST SPECIFICATIONS

 STYLE:
 HANCOCK

 HEIGHT:
 \_\_\_\_'-\_\_\_"

 MAX HEIGHT:
 20'-0"

 BASE:
 16" DIAMETER

MATERIAL:

SHAFT: 4 1/2" DIA. - SMOOTH - ALUMINUM EXTRUSION - .237" WALL BASE: CAST ALUMINUM ALLOY ANSI 356 PER A.S.T.M. B26-95
FINISH: PRIME PAINT THEN FINISH SHERWIN WILLIAMS

ACROLON - PLEASE ADVISE COLOR

ACCESS DOOR: LOCATED IN BASE SECURED WITH TAMPER PROOF

HEX SOCKET SECURITY MACHINE SCREWS

GROUND STUD PROVISIONS: DRILL AND TAP INSIDE WALL OF BASE OPPOSITE ACCESS DOOR TO

ACCOMMODATE A 1/4"-20 GROUND STUD (STUD SUPPLIED BY OTHERS)

ANCHOR BOLTS: (4) 3/4" DIA. X 24" LONG + 3" HOOK (FULLY GALVANIZED WITH

1 GALVANIZED NUT AND 1 GALVANIZED WASHER PER BOLT)

BOLT PROJECTION: 3" REQUIRED


TENON: \_\_\_\_\_" DIA. X \_\_\_\_\_" HIGH



ACCESS DOOR

---16" DIA.---

16'-0"





HALL AND MAIN STREETS - P.O. BOX 19 - SPRING CITY, PA. 19475 PHONE (610) 948-4000 FAX (610) 948-5577 E-mail ADDRESS: sales@springcity.com

DESCRIPTION APSHNC-16-\_\_-S4

PDF